session-hub and model-router

User manual for two Claude Code plugins: coordinating sessions across a hub of repositories, and choosing the model and the effort level of every agent.

Plugin	Version	Marketplace
`session-hub`	0.3.2	`mrbogomips`
`model-router`	0.3.10	`mrbogomips`

Claude Code 2.1.329 or later for the mods; tested on 2.1.329 and 2.1.330. Source: `docs/manual/manual.html` in the plugins' repository; rebuild the PDF with `docs/manual/build.sh`. License: MIT.

Contents

1. The two plugins

- 1.1 What they are and when to use them
- 1.2 Installation
- 1.3 Requirements
- 1.4 Each plugin on its own
- 1.5 Mods on and mods off

2. session-hub

- 2.1 Hub, master and child
- 2.2 Setting up a hub: `setup` and the *Child sessions* section
- 2.3 Deciding: `dispatch`
- 2.4 Starting children: `spawn`
- 2.5 Worked example: one task, two repositories
- 2.6 The children record
- 2.7 Messages and their five types
- 2.8 The guards
- 2.9 Origin marking and the scope line
- 2.10 The `/session-hub` command and the children panel
- 2.11 Limits

3. model-router

- 3.1 The grid
- 3.2 `choose-model`
- 3.3 Project defaults: `setup` and the *Model routing* section
- 3.4 The router mod and the judge
- 3.5 The quality loop
- 3.6 The `/model-router` usage view
- 3.7 The report page
- 3.8 Options
- 3.9 What is recorded, and where
- 3.10 Limits

4. Troubleshooting and FAQ

5. Quick reference

The screenshots were taken from live sessions with invented data: a demo hub with two repositories, `design` and `product`, shown here under `/work/hub`, and six weeks of synthetic subagent records. Paths in them are shortened the same way.

1. The two plugins

1.1 What they are and when to use them

Plugin	What it does	Use it when
`session-hub` 0.3.2	A *master* session opened in a hub of repositories starts one *child* session per repository. Each child gets a written scope, a model and an effort level, talks only to the master and sends requests outside its scope to the master. A hook blocks a child's file writes outside its scope, and the master keeps a record of its children.	Your work spans several repositories kept side by side in one folder, each with its own instructions, skills and agents.
`model-router` 0.3.10	One written grid guides the choice of model and effort level for subagents, child sessions and workflow agents. A mod routes the subagent starts (through the `Agent` tool) that carry no model, and measures on your machine how often each choice was right the first time and what a successful task cost.	You start subagents and want cheap work on cheap models, hard work on strong ones, and numbers to check the choice against.

Why a session per repository? An agent loads the instructions, skills and agents of the folder it runs in. Subagents, `--add-dir` and similar options run from the master's folder and miss the repository's own rules; a child started *in* the repository loads them.

Why a grid? Left to itself, an agent starts every subagent on its own model and effort: simple lookups run on the most expensive model, and hard reviews sometimes run on a cheap one and come back for rework.

1.2 Installation

Both plugins are listed in the `mrbogomips` marketplace. Inside Claude Code:

```
/plugin marketplace add MrBogomips/claude-plugins
/plugin install session-hub@mrbogomips
/plugin install model-router@mrbogomips
```

Or from a shell:

```
claude plugin marketplace add MrBogomips/claude-plugins
claude plugin install session-hub@mrbogomips
claude plugin install model-router@mrbogomips
```

To try a plugin from a checkout of its source without installing it, start Claude Code with `claude --plugin-dir <checkout>/session-hub` (or `/model-router`).

1.3 Requirements

Requirement	Value
Claude Code, for the mods	2.1.329 or later (both plugins declare `engines["claude-code"]: ">=2.1.329"`); tested on 2.1.329 and 2.1.330
Claude Code, for messages between sessions (`session-hub`)	2.1.224 or later on macOS and Linux
Mods	Turned on, for the `session-hub` mod (send guard, shell check, origin marking, scope line, children panel, `/session-hub`) and the `model-router` mod (router, measurement, `/model-router`). The skills and the scope guard hook work without them.
`node`	On `PATH`: the scope guard, the record script, the panel and every `model-router` script run on Node. No dependencies.
Operating system	macOS or Linux

1.4 Each plugin on its own

Each plugin works without the other. Where they meet, a skill names the other plugin's skill in full and checks at run time whether it is installed:

- **Both installed.** `session-hub:spawn` loads `model-router:choose-model` to choose a child's model and effort when neither you nor the hub's *Model* and *Effort* keys did.
- **Only** `session-hub`**.** A child gets the `--model` and `--effort` the master was launched with (without them, Claude Code's defaults), and `spawn` says so in its report.
- **Only** `model-router`**.** It works in any project, with or without a hub. It knows nothing about hubs.

1.5 Mods on and mods off

A *mod* is a module a plugin loads into Claude Code to change its interface or behaviour: a panel, a command, a hook on a tool call. Both plugins ship one, loaded from `hooks/hooks.json`. With mods off:

Part	Mods on	Mods off
`session-hub` skills, scope guard hook, children record	yes	yes
Send guard, shell check, origin marking, scope line, children panel, `/session-hub`	yes	no
`model-router` skills (`choose-model`, `setup`, `report`)	yes	yes
Routing of starts with no model, the coloured 🔀 line under `Agent` calls, measurement, `/model-router`	yes	no

A quick check: type `/session-hub` or `/model-router`. If Claude Code does not know the command, the mod is not loaded (mods off, or a Claude Code version older than 2.1.329).

2. session-hub

2.1 Hub, master and child

Term	Meaning
Hub	A folder that holds several git repositories (as subfolders or submodules), each with its own instructions, skills and agents.
Master	The session opened in the hub. It coordinates and never writes in a child repository.
Child	A Claude Code session started by the master with a repository (or a worktree of it) as its working directory, so that it loads that repository's own rules.
Write root	The one folder where a child may create and change files.
Handoff	What the master writes for each child: role, goal, scope, references, siblings, message rules, first step. A file outside the hub, except in the desktop app, where it is passed inline.
Children record	A JSON file kept by the master outside the hub, with one entry per child.

How a session gets its role

A session is a **child** only when its launch command sets `SESSION_HUB_ROLE=child`; `spawn` does that. A session is a **master** when it runs `session-hub:spawn` or `session-hub:dispatch`; with mods on, the mod also treats a session as master once it runs the record script with a literal absolute `--hub` or `--file`, or when the record for its folder already lists children. Every other session is left alone. No role is inferred from the conversation.

Variable (set by `spawn`)	Value
`SESSION_HUB_ROLE`	`child`
`SESSION_HUB_MASTER`	the master's session name
`SESSION_HUB_SCOPE_ROOT`	absolute path of the write root; it must exist when the child starts
`SESSION_HUB_HANDOFF`	absolute path of the handoff file
`SESSION_HUB_REGISTRY`	absolute path of the children record (a child only reads it)
`SESSION_HUB_GUARDS`	`on` or `off`; absent means `on`

`SESSION_HUB_ROLE` is read without regard to case or surrounding spaces. Any value other than empty, `none`, `master` or `child` makes every guard block, so that a typo cannot switch the guards off.

The three skills

Skill	Side	Does
`session-hub:setup`	master	Writes or updates the hub's *Child sessions* section, after an explicit yes.
`session-hub:dispatch`	master	Decides per repository whether the master reads, a subagent reads, or a child works; handles the children's messages and routes out-of-scope requests; keeps master-only duties.

Skill	Side	Does
`session-hub:spawn`	master	Starts one child per repository with a scope, a model, an effort, the role variables and a handoff; records each child.

You rarely name a skill: ask in plain words ("start a child in product for T-42", "set up session-hub in this hub", "what are the children doing?") and the matching skill loads.

2.2 Setting up a hub: `setup` and the *Child sessions* section

The hub keeps its rules for children in a `## Child sessions` section of its instruction file: `AGENTS.md` at the hub root, or `CLAUDE.md` when there is no `AGENTS.md` (when `CLAUDE.md` is a link to `AGENTS.md`, the skills edit `AGENTS.md`). Every key is optional; without the section, `spawn` uses the defaults and offers `setup` in its report.

Ask "set up session-hub for this hub" in the hub. `setup` looks at the hub (child folders with `.git`, `.gitmodules`, each repository's base branch and role, worktree rules), proposes a section, shows it, and writes it only when you choose *write it*. It does not commit.

Key	Content	Default
Repositories	relative path, one-line role, optionally the base branch	child folders holding `.git`, plus `.gitmodules` paths
Task IDs	the form of a task ID and where tasks live	the ID you give; otherwise a short slug
Propagate	hub rules to quote into the handoff of a child working *outside* the hub (a sibling worktree)	none
Master only	parts of the hub's file and duties that apply to the master only	none
Model	default model per repository or kind of work	none: `choose-model`, else inherited
Effort	default effort per repository or kind of work (`low`, `medium`, `high`, `xhigh`, `max`)	none: `choose-model`, else inherited
Scope	per repository, what a child may read outside its write root	nothing
Registry	path of the children record, outside the hub	`<config dir>/session-hub/children-<hub id>.json`
Guards	`on` or `off` for all three guards	`on`
Permissions	`ask` or `inherit`: what to do when the master bypasses permission prompts	`ask`
Carry	names of more environment variables a child takes from the master's launch	none
Environment	`auto`, `desktop`, `herdr`, `tmux`, `cli` or `manual`	`auto`
Layout	`tabs`, `panes` or `ask`	`ask`
Worktrees	`repo`, `always` or `never`, for children that edit	`repo`
Session name	a pattern for children's names	`<task>-<repo>`

What you say in the conversation beats the keys, and the keys beat the defaults. An example section:

```
## Child sessions

Settings for the session-hub plugin. The invocation says which repositories a piece of
work touches.

- Repositories:
  - `design/`: specification and API documents, base branch `main`
  - `product/`: code monorepo, base branch `develop`
- Task IDs: `T-123`, listed in `backlog/tasks.md`
- Master only: the sections *Backlog* and *Meetings* of this file; writing the story
tracker
- Model: design: opus; product: sonnet; read-only: haiku
- Effort: product: medium; read-only: low
- Scope:
  - product: `design/docs/api/`
- Environment: auto
- Layout: panes
- Worktrees: repo
- Session name: `<task>-<repo>`
```

Model and *Effort* take values per repository (the folder name) or per kind of work (`read-only`, `editing`, or a word the hub uses); a repository match beats a kind match. A *Scope* entry lets a child of that repository read those files; it does not let it analyse or change the other repository. A *Registry* path inside the hub is refused: state lives outside the hub.

2.3 Deciding: `dispatch`

In the master, a task that touches the hub's repositories goes through `dispatch`. It reads the *Child sessions* section, reconciles the children record with the live sessions, resolves which repositories the work touches (it asks when unsure, and never guesses), then picks the first row that fits for each:

Situation	Action
A child for that repository and task is already running	Message that child (`[master] …`); no second child
Any write in the repository	A child, with `session-hub:spawn`
A read that needs the repository's own skills or rules to interpret	A read-only child
A broad read whose result is a conclusion	A read-only subagent of the master
A few known files to read	The master reads them itself

More than about five files, a search of the repository or its build tools is no longer "a few known files". A read that turns into a change becomes a child. `dispatch` states its decision in a short table, then starts all the children in one `spawn` call, so that their handoffs name each other as siblings.

2.4 Starting children: `spawn`

For each child, `spawn`:

1. resolves the repository and its base branch, and reads the hub configuration;

2. reconciles the children record (a child recorded as live but no longer listed becomes `lost`);
3. looks for a live child on the same repository and task, and sends it the request instead of starting another;
4. picks the environment, the name, the worktree and the write root, and the scope;
5. chooses the model and the effort: what you said, then the hub's *Model* and *Effort* keys, then `model-router:choose-model` when installed, otherwise the `--model` and `--effort` the master was launched with (none when it set none);
6. writes a handoff file outside the hub (`<name>-handoff.md` in the harness's scratchpad or a new `mktemp -d` folder) and starts the child with a one-line prompt, `Read and follow <file>`;
7. records the child as `running`, and reports per child: name, repository, write root, model and effort, environment, how to open it, and the caveats that apply.

Environments

`spawn` takes the first environment that applies, unless the hub's *Environment* key names one.

Environment	Detected when	Starts the child with	Scope guard
Desktop app	a session-starting tool such as `start_session` is available	the tool, with the repository as working folder	**inactive**
Herdr	`HERDR_ENV` is `1` and `herdr` is on `PATH`	a tab or pane with `--env`, then `herdr agent start`	active
tmux	`TMUX` is set and `tmux` is on `PATH`	a window or pane running the command, given as arguments	active
Terminal	`claude --help` lists `--bg`	`claude --bg` from the repository	active
Manual	none of the above	commands and a handoff handed to you	active if run as given

The launch command

A child starts the way the master was started, so that it uses the same account and configuration folder (two sessions with different configuration folders cannot message each other) and the same permission mode. If you start Claude Code through an alias or a wrapper that picks a profile or adds flags, the children get the same. `spawn` runs `scripts/launch.mjs`, which reads the master's own process and environment, and builds:

- **carried flags** that configure the session (`--settings`, `--mcp-config`, `--plugin-dir`, `--setting-sources`, `--agent`, `--append-system-prompt`); the master's own (`--name`, `--resume`, `--worktree`, `--add-dir`, a prompt…) are left out;
- **identity variables**: `CLAUDE_CONFIG_DIR`, `SHALLOW_PROFILE` and the `XDG_*_HOME` folders when set, `HOME` when it differs from the account's home, and the variables you name under `Carry`; nothing else from the environment, and never a credential;
- **child flags**: `-n <name>`, `--model`, `--effort`, the permission flags, `--add-dir <handoff folder>`, then `--` and the prompt;
- the **role variables**, placed as each environment allows.

Children start in the master's permission mode, because messages between sessions that differ on bypassing permission prompts wait for your approval. When the master bypasses permission prompts, `spawn` asks at every start which mode the children get. With `Permissions: inherit` in the

hub's section it does not ask: the children bypass permission prompts like the master, and the report says so.

After each start `spawn` checks that the child appears in the session list. A child that started under another configuration folder does not: it would use another account and could not be reached by message, so `spawn` sends it no work and tells you. With mods on, such a child also says so itself, in its first lines and in `/session-hub`.

Worktrees and the write root

Where the worktree lives	Who makes it	Write root
No worktree (read-only child, or `Worktrees: never`)	—	the repository
Under the repository (for example `<repo>/.claude/worktrees/…`)	the child, as its repository's policy says	the repository
In a sibling folder (`<repo>-worktrees/<name>`)	the master, before the start (`git -C <repo> worktree add …`)	the worktree

Making a sibling worktree is the only thing the master does in a repository. A background child (`claude --bg`) moves into a worktree under `<repo>/.claude/worktrees/` before its first edit, unless the repository sets `worktree.bgIsolation` to `"none"`.

Names and layout

Names come from the *Session name* pattern, lowercased, limited to `a-z0-9_-`, starting with a letter, at most 24 characters, with `-2`, `-3`… when taken. With `Layout: ask` (the default), `spawn` asks for tabs or panes and whether to save the answer as the hub's default; with more than four children in a stack of panes, the rest open as tabs. In Herdr, a child stopped at a trust prompt makes `herdr agent start` return `agent_not_ready`. In the desktop app, archiving a child session can lose its uncommitted changes.

2.5 Worked example: one task, two repositories

The hub `/work/hub` holds `design` (the API specification) and `product` (the code), with the section shown in 2.2. Task T-42: add a CSV export endpoint to `product`, and document its size limit in `design`. The master runs in tmux, in a session named `hub` (`claude -n hub`). The hub sets `- Session name: \`t<number>-<repo>\``, so T-42 gives `t42-product`; with the default pattern `<task>-<repo>` the name would be `t-42-product`. The screenshots' children (`t123-…`) follow the same pattern. You type:

```
T-42: add GET /export to product (CSV, at most 10 000 rows) and document the limit in
design/docs/api/export.md.
```

`dispatch` loads, reconciles the record and states its decision:

```
| Repository | Action           | Why                                    |
|------------|------------------|----------------------------------------|
| product    | child (editing)  | writes code and tests                  |
| design     | child (editing)  | writes the API document                |
```

It then calls `spawn` once for both. With the hub's keys, `t42-product` runs on `sonnet` at `medium` and `t42-design` on `opus` (no *Effort* key for design, so `choose-model` chooses it when installed, or the master's is inherited). With `Layout: panes`, the first child opens to the right of the master and the next one below it:

```
tmux split-window -h -d -t "$TMUX_PANE" -c /work/hub/product -P -F '#{pane_id}' \
  -e SESSION_HUB_ROLE=child -e SESSION_HUB_MASTER=hub -e
SESSION_HUB_SCOPE_ROOT=/work/hub/product \
  -e SESSION_HUB_HANDOFF=<dir>/t42-product-handoff.md \
  -e SESSION_HUB_REGISTRY=<config dir>/session-hub/children-<hub id>.json -e
SESSION_HUB_GUARDS=on \
  -- claude -n t42-product --model sonnet --effort medium --permission-mode default \
  --add-dir <dir> -- 'Read and follow <dir>/t42-product-handoff.md'      # prints %12
tmux set -p -t %12 @session_hub_child t42-product
tmux set -p -t %12 remain-on-exit on
```

tmux runs the command after `--` as it is, with no shell in between, so a carried value such as a JSON `--settings` reaches the child as written. The pane option `@session_hub_child` names the child for the master's later checks; the pane title is not used, because Claude Code replaces it with its own.

The same child in the other environments:

```
# Herdr: the variables go on the pane, then the agent starts in it
herdr pane split --current --direction right --cwd /work/hub/product --no-focus \
  --env SESSION_HUB_ROLE=child --env SESSION_HUB_MASTER=hub ...
herdr agent start t42-product --kind claude --pane <pane-id> -- -n t42-product --model
sonnet ...
herdr agent prompt t42-product "Read and follow <dir>/t42-product-handoff.md"

# Terminal: a background session, opened with `claude attach t42-product`
cd /work/hub/product && env SESSION_HUB_ROLE=child ... claude --bg -n t42-product --model
sonnet ... \
  -- "Read and follow <dir>/t42-product-handoff.md"
```

The handoff (abridged) tells the child everything it needs and nothing it loads by itself:

```
# T-42: CSV export endpoint (product)

2026-11-20 · /work/hub/product · base branch develop · task T-42

## Session
Your role is `child` of the master `hub` (ref `8f2c1a`). Model sonnet, effort medium: the
hub's Model and Effort
keys for product.
## Goal
Add `GET /export`, which returns the filtered records as CSV. Done when a PR is open on
`develop` with tests.
## Scope
- Write root: /work/hub/product
- Task: the endpoint and its tests; no change to the record model or to other endpoints.
- External references (read only): /work/hub/design/docs/api/export.md
## Siblings
`t42-design` (/work/hub/design) owns export.md. If the columns must change, ask the
master first.
## Messages
The master is `hub`: `SendMessage` to `hub`. Start every message with `[T-42 product]
<type>:` ...
## Rules
- You write only under your write root. ...
## First step
Read export.md, then write the failing test for `GET /export`.
```

The report ends with each child's name, repository, write root, model and effort, environment and how to watch it (here: its pane). While the children work, the master hears them through their messages and through `SendMessage` with `notify_when_idle`; it never polls. When `t42-product` needs the document changed, it sends `[T-42 product] out-of-scope: …`; the master routes it to `t42-design` and tells `t42-product` what will happen. When a child opens a pull request it sends `[T-42 product] pr: <url>`, and `done` when finished.

> **First run in a repository.** Folder trust is not inherited by a repository nested in a trusted hub. A child may stop at the trust prompt in its own window, and `claude --bg` fails with `Workspace not trusted`. These prompts are yours to answer; `spawn` never answers them.

2.6 The children record

The master keeps one JSON file per hub, outside the hub:

```
<config dir>/session-hub/children-<hub id>.json
```

`<config dir>` is `CLAUDE_CONFIG_DIR` when set (absolute, or starting with `~`; a relative one is refused), else `~/.claude`; `<hub id>` is the first 16 hexadecimal digits of the SHA-256 of the hub's real path (NFC). The hub's *Registry* key can name another path outside the hub; a path that lands inside the hub, even through a link or a folder not made yet, is refused. The folder is created with mode `0700`, the file with `0600`. One entry per child:

```
{
  "name": "t42-product",
  "repo": "/work/hub/product",
  "task": "T-42",
  "scope": { "writeRoot": "/work/hub/product", "external":
["/work/hub/design/docs/api/export.md"] },
  "model": "sonnet", "effort": "medium",
  "status": "running",
  "started": "2026-11-20T10:00:00.000Z",
  "lastMessage": { "type": "pr", "at": "2026-11-20T11:30:00Z", "text":
"https://example.com/pr/1" },
  "requests": [{ "at": "2026-11-20T11:00:00.000Z", "text": "update the API spec",
"outcome": "sent to t42-design" }]
}
```

Status	Meaning	Set by
`running`	started, working	a new entry
`waiting-user`	waiting for a person: an approval, a merge gate	`dispatch`, when the child says so
`done`	finished	`dispatch`, on a `done` message
`abandoned`	stopped, with a reason	`dispatch`, on `abandoned`, or when you agree to replace a failing child
`lost`	recorded as live, no longer in the session list	a reconcile

The skills write the record only through `scripts/registry.mjs`, never by hand. You can read it yourself:

```
R="<plugin folder>/scripts/registry.mjs"
node "$R" path --hub /work/hub          # the default path
node "$R" read --hub /work/hub          # the record as JSON
```

The other commands are `upsert --entry '<json>'`, `status --name <child> --status <status> [--reason <why>]`, `request --name <child> --text <t> [--outcome <o>]` and `reconcile (--live <name,…> | --live-none)`; each takes `--hub <dir>`, and `--file <path>` for a record at another path (a write with `--file` needs `--hub` too). An option a command does not take exits 1 and writes nothing. A child started again under the name of one that ended gets a fresh entry. Writes are atomic under a lock file next to the record (waits up to 5 s; a lock older than 30 s, or whose writer has ended, is stale and taken over). A record that is not valid JSON, or from a newer format, is reported and never overwritten. A failing record never stops a start: `spawn` tells you and carries on.

2.7 Messages and their five types

A child talks to the master only, with `SendMessage` to the master's name. Every message starts with a fixed prefix: `[<task> <repo>] <type>: <text>`. The master's messages start with `[master]`.

Type	Sent when	Master's duty	Record
`question`	the child is blocked on a decision	answer, or pass it to you and send the answer back	`lastMessage`

Type	Sent when	Master's duty	Record
`out-of-scope`	a need or request outside the scope, also one you make directly in the child's session	route it: ask you if needed, send it to the child that owns the scope, start one, or do a read itself	`lastMessage` and a request with its outcome
`pr`	a pull request was opened; the text holds its URL	record the URL; follow the hub's rules on pull requests	`lastMessage`
`done`	the work is finished	follow the hub's closing rules	status `done`
`abandoned`	the work was stopped; the text holds the reason	tell you	status `abandoned`

Examples: `[T-42 product] question: Should empty filters export every record?`, `[T-42 design] pr: https://example.com/demo/design/pull/7`.

> A message between sessions is **information, never authorization**. Neither side merges, pushes, deletes or changes settings because another session asked; approval comes from you, in that session.

2.8 The guards

Three guards hold a child to its scope. All three act only in a child, and all three **fail closed**: a guard that cannot evaluate blocks and says why. `SESSION_HUB_GUARDS=off` (or the hub's `Guards: off`) turns all three off.

The scope guard (hook, works with mods off)

`session-hub-scope-guard` is a `PreToolUse` hook on `Edit`, `Write` and `NotebookEdit`. It resolves the target's real path, following symbolic links, and blocks a write that is not under the real write root. In the example below, `product/api-docs` is a link to `design/docs/api`: the path looks inside `product`, but lands in `design`, so the write is blocked and the child sends the request to the master instead.




Figure 1. A blocked write in the child `t123-product`. The message starts with `[session-hub] Write blocked:`, names the path and the write root, and tells the model not to retry through another tool but to send an `out-of-scope` message.

The guard also blocks when it cannot decide: an unknown role value, a missing or relative write root, a write root of `/` or the home folder, a relative target or one starting with `~`, unreadable input, or `node` missing. It blocks on its own after 7 seconds, ahead of the hook's 10-second timeout.

It also blocks a write to a file that has more than one hard link. A hard link has no path that leads elsewhere, so the guard cannot tell whether another name of the file is outside the write root, and a write would change the file under every name.

It blocks a write to the repository's Claude Code settings, `.claude/settings.json` and `.claude/settings.local.json` under the write root, and so does the shell check. Their `env` and hook settings would turn the child's guards off at its next start. The settings of a repository are the master's: the child sends the change to the master as an `out-of-scope` request.

The shell check (mod)

Best effort, mods on only. Before a `Bash` (or `Monitor`) command runs in a child, the mod reads its redirections and the targets of `tee`, `touch`, `mkdir`, `rm`, `rmdir`, `truncate`, `unlink`, `cp`, `mv`, `ln`, `install`, `sed -i` and `find` (`-delete`, `-fprint` and the like, and the command of `-exec`, `-execdir`, `-ok` and `-okdir`), resolves them (relative ones against the session's folder, or the folder of an earlier literal `cd` in the same command) and denies a target outside the write root. `/dev` and the system temporary folders are allowed. The command is read as bash or zsh would read it (the `Bash` tool runs zsh on macOS), zsh's `>!`, `noglob`, `repeat` and `=command` included. The commands inside substitutions (`$(…)`, backticks, `<(…)`, also in double quotes and in here-documents whose delimiter is not quoted) and the literal line given to `eval` or `sh -c` are judged too. A hard link to a file outside the write root is denied, and so is a write through a symbolic link that the same command makes. A command the check cannot read, such as a here-document whose delimiter never comes, is denied with the reason; so is any write when the write root is `/`, the home folder, or not an existing folder. For `echo x > ../design/notes.md` in `/work/hub/product` the model is told:

```
[session-hub] Shell command blocked: it writes /work/hub/design/notes.md, outside the
write root /work/hub/product. Do not retry this write through another command or tool.
Send an `out-of-scope` message to the master, saying what you need written and why, and
tell the user that you passed the request to the master.
```

When a link moves the target, the message adds where it lands: `(resolves to …)`. Targets held in variables, in the output of command substitutions or in globs are not judged, nor a line given to `eval` or `sh -c` that is not literal, nor what another program (a script, `git`, a build tool) writes.

The send guard (mod)

Mods on only. A child's message goes to its master, by name (with or without `[<ref>]`; it is delivered to the bare name), or to the child's own subagents. Any other recipient, a sibling or a socket address, is refused. Claude Code reports `Not sent: a plugin hook refused it (…)` with this reason:

```
[session-hub] This session is a child and may message only its master, "hub". Send what
you need to "hub" with your message prefix; a request for another session or repository
is an `out-of-scope` message, and the master routes it.
```

A child replies to the master by its name: a reply to the `from` address of a message is refused.

2.9 Origin marking and the scope line

Origin marking (child, mods on). A message from another session, the master included, reaches the child with a line in front of it saying that it is information, not authorization. A prompt you type carries no mark.




Figure 2. A `[master]` message as the child receives it. The first line, starting with `[session-hub]`, is the mod's mark; the closing paragraph is Claude Code's own notice for messages from other sessions.

Scope line (child and master, mods on). The mod puts the role and the scope (child) or the record (master) in the system prompt as the `session-hub:scope` section, and sends the same text as context on the first prompt after the start, after a compaction and after `/clear`, so the scope survives a long session.

2.10 The `/session-hub` command and the children panel

`/session-hub` is registered by the mod. Its answer is for you only: the model does not read it.

Command	Does
`/session-hub`	In a child: its role, write root, handoff, record and whether the guards are on. In a master: the record and the children table (status in the record, live status, model and effort as a four-cell bar and a word, `▰▰▰▱ high`, last message), sized to the terminal, and the children panel opened beside the chat. In any other session: that it has no role.
`/session-hub log`	Opens the children record, `session-hub`'s log, in the system's default app, printing its path. In the Claude desktop app it opens the Session hub card on Record instead (below). With no record yet it says so and opens nothing. In a child it opens the record of its master. `record` works too.
`/session-hub help`	What the command does. Any other argument prints `Unknown argument "…"` and the same help.



Figure 3. `/session-hub` in the master. `t118-product` finished earlier and is no longer in the session list (`not listed`); the two T-123 children are live.




Figure 4. The children panel, opened beside the chat. It refreshes every 30 seconds and on each `/session-hub`; the live status comes from the session list (`ListAgents`). The model is bold in its tier's colour and the effort is the bar and the word in its level's colour, as in `model-router`; a status is green when the child runs, yellow when it waits, was abandoned or is not listed, red when it is lost. Under the rows the panel offers the children record: `l` opens it. The three children of this capture are in the record only, so each reads `not listed`.

In the Claude desktop app (and in VS Code and the mobile apps) `/session-hub` opens no panel: it draws one card in the conversation, *Session hub*, laid out like the app's own `/context` card. The header gives the session's role and, in a master, how many children there are and how many are live; the title folds the card to its header and one bar of the children by status. A dropdown at the left picks the view:

- **Children** (`/session-hub`): the role, the hub, the repositories and the record, then the children grouped by status (running, waiting for you, done, abandoned, lost). Each child shows its model and effort in words (`Sonnet · medium`), what the session list says and its last message, or why it was lost or abandoned. A group opens on its name, one at a time; a group of more than twelve children counts the rest. In a child the card shows its master, its write root and handoff by name, and whether the guards are on.
- **Record** (`/session-hub log`): how many children, events and requests, when the first child started, and the latest seven events (starts, messages and requests, with what was decided about each); a dropdown at the right narrows them to one child.

The two views read the same children record and answer different questions. **Children** is the state now: one row per child, with its status, its model and effort, and what the live session list says about it. **Record** is the history: what happened and when, as counts and a timeline of starts, last messages and requests with their outcomes, newest first. Children shows who is working; Record shows what has happened so far.




Figure 4b. The Session hub card in the Claude desktop app, on Children: the role, the hub, the repositories and the record, then the children by status, the Running group open.




Figure 4c. The same card on Record: the counts and the latest events of the record, with the child picker at the right.

The record file is linked in the card's last line. The newest card follows the 30-second refresh; the cards before it keep their header and bar, and older ones are plain text.

In the master, a `Bash` call that starts children gets one line per child under its row, in the same colours: the model, the effort and the child's name, for example `└ 🔀 opus ▰▰▰▱ high -> t123-product`. The mod reads them from the launch command that `spawn` writes (`--model`, `--effort` and `-n` of the `claude` command, also inside `tmux send-keys`, or the flags after `--` of `herdr agent start`); a command that names neither model nor effort gets no line. In the Claude desktop app the line is one quiet line in words, `Started t123-product on Opus · high`, and a child started with the app's own session tool gets no line at all: the app's session card already names it.




Figure 5. `/session-hub` in the child `t123-product`.




Figure 6. `/session-hub help`.

In a session with no role the answer is: `This session has no session-hub role. It becomes a master when it uses session-hub:spawn or session-hub:dispatch.` With mods off there is no command; the record stays readable at its path (2.6).

2.11 Limits

- **Shell writes are covered on a best-effort basis, and only with mods on.** The hook sees `Edit`, `Write` and `NotebookEdit`; the shell check reads the command line only. With mods off, a shell write is held back by the handoff alone.
- **The desktop app has no guard.** Its session tool takes no environment variables, so a child started there has no role: the scope holds by the handoff alone, and `spawn` says so. Model and effort on the app's start tool are unverified.
- **The send guard needs mods on.** With mods off, a sibling can still be messaged; the master-only rule is then prose in the handoff.
- **A child resumed without its variables is no longer a child.** `claude --resume` typed without the `SESSION_HUB_*` variables leaves the hook and the mod inactive.
- **A killed hook lets the write through.** Claude Code treats a hook killed or past its timeout as a non-blocking error; the guard's own 7-second limit covers a slow guard, not a killed one.
- **Trust is per repository** (see 2.5).
- **An organization's managed mod can skip parts of the mod.** A managed mod that runs first can pass an event on without the plugin's hooks; Claude Code then shows lines such as `session-hub: its prompt.compose hook was skipped`. The scope line then rides prompts as context, and a compaction is told from the context's size.
- The panel's live status comes from the session list; a child the list does not show reads `not listed`.

3. model-router

Component	Kind	Does
`model-router:choose-model`	skill	The grid. Meant to load whenever the agent is about to start a subagent, a child session or a workflow, so that it passes a model and an effort explicitly.
`model-router:setup`	skill	Writes a project's *Model routing* section, after your yes.
`model-router:report`	skill	Builds and opens the quality report page.
`model-router`	mod	Routes subagent starts that carry no model; draws the 🔀 line under each `Agent` call with the model and effort the subagent got; records decisions, starts, signals and reports. Fails open.
`/model-router`	command (mod)	The usage view, routing on or off, the report.

3.1 The grid

Model tiers

Go down the table and stop at the first row that fits.

Tier	Fits when	Examples
`haiku`	Simple, repetitive work whose result is easy to check, with no judgment calls.	List or summarize files; run a single command; rename a symbol; apply the same edit in many places
`sonnet`	What done looks like fits in one sentence.	A well-specified change across a few files; tests for existing code; a bug whose cause is described
`fable`	Large **and** open-ended work where judgment and accuracy really matter. Both must hold.	A complex design; an architecture decision with long-lasting consequences
`opus`	Everything else, and any time you hesitate between two tiers.	A review; debugging when the cause is unknown; most coordination work

The tier names are aliases; which model sits behind each is configuration. By price, cheapest first: `haiku` < `sonnet` < `opus` < `fable`. "One tier up" follows this order.

Effort

Ask in order and stop at the first yes:

1. Is it a simple task or a quick exchange? → `low`
2. Is it long, hard and critical, **and** does it run unattended? All three. → `xhigh`
3. Would an unnoticed mistake cost money, a client or a wrong decision? → `high`
4. None of the above. → `medium`

Never `max`.

Task classes

Class	Covers	Usual choice (prior)
`read-search`	find files, symbols or facts	`haiku` · `low`
`read-analyze`	read and conclude: explain, compare, summarize	`sonnet` · `medium`
`edit-mechanical`	repetitive edits that are easy to check	`haiku` · `low`
`edit-specified`	a change whose done-state fits in one sentence	`sonnet` · `medium`
`review-debug`	review, or debugging with an unknown cause	`opus` · `medium`
`design-open`	open-ended design where judgment matters	`fable` · `high`

When none fits, the closest one is used; no class is invented. `review-debug` and `design-open` are never taken below the grid by quality hints.

Rules around the grid

- **In doubt, go up.** Rework costs more than the saving.
- **Risk belongs to the act, not the topic.** Changing production, moving money or altering data that cannot be restored is risky; writing or testing code about such things is not. A risky start gets at least `high` effort and the `!` marker on its tag.
- **Sessions: choose at the start.** A running session's model is never changed.
- **Escalate one step at a time.** Retry with specific feedback; then raise the effort one level; then start one tier up with a handoff.
- **A coordinator's own model.** A session that mostly delegates runs on `opus` at `medium`, unless its own design work is hard.
- **Inline or delegate.** A small task whose files are already in context is done inline.
- **Continue, do not restart.** A follow-up goes to the subagent already started on the topic.

3.2 `choose-model`

The skill's description makes the agent load it when it is about to start work on another model; a start that skips it is caught by the router (3.4). The first rule that gives a value wins:

1. an explicit choice by you, in the conversation;
2. the project's *Model routing* section, when it names the kind of work or the class;
3. the grid.

An agent definition that fixes its own model or effort keeps it, whatever the project's section or the grid say: unless you name one for it, the agent passes only what the definition leaves open. It reads the frontmatter of a project or user agent (`.claude/agents/<type>.md`, else `agents/<type>.md` in the configuration folder), and passes neither value to an agent it cannot check, such as a plugin's.

Before each start the agent writes one line, passes `model` and `effort` on the start call, and begins the description with the class tag. The line is 🔀 , the model, an effort bar of four cells (▰ filled, ▱ empty: one for `low`, two for `medium`, three for `high`, four for `xhigh`), the effort, `->` and the reason in under 12 words:

```
🔀 haiku ▰▱▱▱ low -> find callers of parseConfig, easy to check
→ Agent  model: haiku  effort: low  description: "[mr:read-search] Find callers of
parseConfig"

🔀 sonnet ▰▰▱▱ medium -> CSV endpoint with tests, done-state is clear
→ Agent  model: sonnet  effort: medium  description: "[mr:edit-specified] Add GET /export
with tests"

🔀 opus ▰▰▰▱ high -> rotating the production key cannot be undone
→ Agent  model: opus  effort: high  description: "[mr:edit-specified!] Rotate the
production API key"
```

This line is plain text and works with mods off. With the mod on, the same line is also drawn in colour under each `Agent` call's row, with what the subagent *actually got* after routing (3.4):




Figure 7. Three subagents started from a `sonnet` session. The first carried no model: the judge lowered it to `haiku` at `low`. The second named `opus` at `high`, which the router keeps. The third carried no model either: the judge kept `sonnet` and set the effort.




Figure 7b. In the Claude desktop app the same line is one quiet line under the `Agent` row, in words: the model and effort it got, then the reason.

The colours: the model in bold, `haiku` white, `sonnet` light blue, `opus` blue, `fable` orange; the effort bar and word by level, `low` green, `medium` yellow, `high` orange, `xhigh` red, with the empty cells dark grey; the reason dim. The reason names the case:

- `explicit`: the call named the model;
- `fixed`: the agent's definition fixes it;
- `judge: <class>; …` with what the router changed: `lowered from opus`, `raised from haiku`, or `kept sonnet`, followed by `, effort set` when only the effort was set. With no class tag and no class from the judge, the judge's tier (`balanced`) or `no class` stands in its place;
- `judge: risky work; raised from <tier>`: risky work sent to the deep tier;
- `keep: <why>`: the router left the start alone (routing off, a fork, a session-wide subagent model, a judge error).

An effort that nobody set shows four empty cells and a dim `default` until the subagent's first model request; if that request carries no effort level either (a model without effort levels), the line keeps `default`. A model id outside the four tiers is shown as it is, without colour. The line never replaces the row: when it cannot be drawn, the row is drawn alone.

For a child session, `session-hub:spawn` loads the skill and puts the result on the launch command as `--model <tier> --effort <level>`. For a workflow, the skill chooses per agent, one line each.

Quality hints. When `<config dir>/model-router/quality/recommendations.json` exists, the skill reads the entry for the class as a hint; it never overrides the order above, never goes below the grid for `review-debug` or `design-open` or below the project's defaults, and does not apply to a risky start. Releases up to 0.3 do not write this file.

3.3 Project defaults: `setup` and the *Model routing* section

Ask "set up model routing for this project" (or "always use opus for migrations"). `setup` finds the instruction file (`AGENTS.md`, the target of a `CLAUDE.md` link, or a plain `CLAUDE.md`), asks about defaults and exceptions, suggests some from the repository (migrations, infrastructure, billing, generated code, bulk refactors), shows the exact section and writes it only after your clear yes. Values stay inside the grid: models `haiku`, `sonnet`, `fable`, `opus`; effort `low`, `medium`, `high`, `xhigh`; the six classes. It does not commit.

```
## Model routing

Defaults for `model-router:choose-model`. An explicit choice in the conversation still
wins; anything not
listed here follows the grid.

- Default: the grid
- Coordinator: `opus` · `medium`

| Kind of work | Class | Model | Effort | Why |
|---|---|---|---|---|
| Database migrations | `edit-specified` | `opus` | `high` | data cannot be restored |
| Bulk renames across the codebase | `edit-mechanical` | `haiku` | `low` | checked by the
compiler |
```

3.4 The router mod and the judge

The skill makes the agent pass a model; the mod catches the starts that still carry none. At each subagent start through the `Agent` tool:

The start	The router
carries a model, is a fork or a resume	keeps it
names an agent whose definition fixes a model, a plugin's agent, or one whose definition it cannot read (a file under the agent's name that declares another `name` is not its definition)	keeps it
names an agent whose definition declares an effort (`effort:` in its frontmatter)	keeps that effort, risky work included, and routes only the model if the definition fixes none
runs with routing off, or under a session-wide subagent model (`CLAUDE_CODE_SUBAGENT_MODEL`)	keeps it
carries no model	asks the judge, then sets the model and the effort

The judge is one call to the fast tier (default `haiku`, 8-second limit) with a prompt generated from the grid. It receives the subagent type, its short description and the first 4,000 characters of its task, and answers a tier, an effort, a class, a risk and its confidence. The router then:

- lowers the model only at confidence ≥ 0.6 (`minDowngradeConfidence`), raises it at ≥ 0.3 (`minUpgradeConfidence`);
- raises it to the frontier tier (`fable`) only for a task of class `design-open` at confidence ≥ 0.7 (`minFrontierConfidence`); any other frontier answer counts as the deep tier;
- sends risky work (risk > 0.7, or a `!` tag) to the deep tier with at least `high` effort;
- leaves the start unchanged on a judge error, a timeout or an unreadable answer (logged as `error`), except a start tagged `!`, which still goes to the deep tier.

Decisions are logged with an action: `downgrade`, `upgrade`, `keep`, `explicit`, `forced-risk` or `error`. Under the call's row the mod draws the 🔀 line of Figure 7 with the model the subagent started on, its effort and the reason.

What it never touches. The start call itself is never changed: the model is set when the subagent starts and the effort on each of the subagent's model requests, so routing works in every permission mode, auto mode included. An effort the call already carries is kept. Starts made by a plugin's own code and workflow agents are measured, not routed. Of the built-in types, only `general-purpose` and `Explore` are routed. Risky work goes to the deep tier, never to the frontier one.

Turn routing off for one session with `/model-router off` (and back with `on`), or for good with the `routeSubagents` option.

3.5 The quality loop

So far the router only *measures*; choosing from the data is planned for a later release. Here is what is measured, in plain words.

A task and its outcome

Each subagent start is one **task**. Its outcome is fixed when its **rework window** closes: 30 minutes after the subagent's report (`reworkWindowMin`), or the end of the session.

Outcome	When
`success`	the subagent reported and nothing in the window redid its work
`rework`	in the window, the main session or another agent wrote one of its files; or a similar start of the same class followed on the same files; or the same subagent was sent a correction after its report; or one of the next two prompts you typed named its files or its task
`failure`	it failed, or was stopped by its parent and redone
`cancelled`	no report (for example, the session ended first), or stopped

"Similar" means that the distinct words the two texts share are at least half of all the distinct words in both (`similarityThreshold` 0.5), ignoring common words such as *the* and *to* and the class tag. A task that never reports is closed as `cancelled` after 24 hours.

The numbers

Measure	Meaning
First-pass yield (FPY)	success ÷ (success + rework + failure): how often the work was right the first time. A cancelled task is not scored: the views leave it out of every count, FPY and cost.
Rework rate	rework ÷ (success + rework + failure)
Cost per task	the mean estimated cost of a task, from the engine's own estimate
Cost per successful task (`$/success`)	cost per task ÷ FPY: what one good result really costs, rework included. A cheap model that is often wrong can cost more per success than a dearer one.

The numbers are kept in **cells** of class × tier × effort (for example `edit-specified · sonnet · medium`), at two **levels**: you across all projects (user), and each project. A project is identified by its git remote, else its root folder. Aggregates are aged with a 30-day half-life (`halfLifeDays`), so old work weighs less.

What is learned

Cancelled tasks, risky tasks, tasks with no class (no `[mr:<class>]` tag and no judge answer), tasks on a model outside the four families and tasks with no known effort are recorded but not learned. Read-only classes and cells with fewer than five tasks are **weak signals** and are flagged.

Recommendations

For each class, the recommended cell is the one with the lowest cost per successful task among the cells with at least three tasks, never below the grid for `review-debug` and `design-open`; with no such cell, the grid's usual choice stands. A recommendation that differs from the grid is marked `(differs)`. In 0.3 it is information only: the router does not act on it.

Class tags

The class comes from the tag at the start of the description, `[mr:<class>]`, or `[mr:<class>!]` for a risky start; without a tag, from the judge's answer. Tag your own starts when you write them by hand: an untagged start that the router does not judge has no class and is not learned. The tag is read in any case and with spaces inside; a class that is not in the grid gives no class, but its `!` still makes the start risky.

Compaction

The mod appends records to `events.jsonl`. **Compaction** (at session start, when the view opens or refreshes, and before the report) closes the tasks whose window ended, appends their outcomes and folds them into the aggregates. It is safe to repeat: a task is never counted twice.

3.6 The `/model-router` usage view

Command	Does
`/model-router`	Opens the usage view on Overview, last 7 days, user level

Command	Does
`/model-router [overview|models|classes|decisions|savings] [24h|7d|30d|all] [user|project]`	Opens it on that tab, window and level, in any order (`stats` works as `classes`)
`/model-router on`, `/model-router off`	Turns routing on or off for this session
`/model-router report`	Writes and opens the report page, and prints its path; in the Claude desktop app, opens the card on Trend
`/model-router log`	Opens the event log (`events.jsonl`) in the system's default app, printing its path; in the Claude desktop app, opens the card on Log
`/model-router help`	Lists the arguments and the keys; any unknown argument does the same

For example, `/model-router classes 30d project` opens Classes over the last 30 days for this project.

The view is a dialog laid out like Claude Code's own Settings dialog: a header row with 🔀 `model-router` and the four tabs, a second row with the window (24h, 7d, 30d, all) and the level (`user · project`), the content, and a footer of key hints. The active tab and window are drawn as a teal block, and the KPI tiles have teal borders. In a wide terminal with the fullscreen layout the view docks beside the chat; otherwise it opens above the prompt.

In the Claude desktop app (and in VS Code and the mobile apps) `/model-router` opens no pane: it draws one card in the conversation, *Model routing*, laid out like the app's own `/stats` card. The header gives the window's right-first-time rate and cost per success; the title folds the card to its header and one bar of the window's tasks by model. A dropdown at the left picks the view, two at the right the scope (all projects or this one) and the window:

- **Overview**: a heatmap of tasks per day over 22 weeks; right first time, cost per success, the share redone, tasks scored, the model used most and the busiest day; the routing decisions by kind with their total; one sentence on the change from the period before.
- **Models**: a row per model, Opus darkest to Haiku lightest, with its share of tasks and, under it, its right-first-time rate, its cost per success and each effort level's count and rate; tasks per day by model.
- **Task classes** and **Projects**: a row each, with the same figures.
- **Decisions**: the decisions by kind (moved to a cheaper model, moved to a stronger one, kept as asked, model named in the call) with the latest of the kind you open.
- **Savings**: whether routing pays off. A verdict in one sentence; the cost per success against the cost of the same tasks on the model of the session that started them, the amount saved and spent, right first time for the tasks moved and for those kept, and the judge's calls and time; where the tasks ran (moved to a cheaper model, kept, moved to a stronger model); the spend per week; the saving per pair of models, with a total.
- **Trend**: right first time and cost per success per week, as bars; its last line links the report page (section 3.7).
- **Log**: the event log by kind and over time (by hour for the last 24 hours), with the latest records of the kind you open, and `events.jsonl` linked in its last line. No prompt text is shown.

The arguments open the card on a view, a window and a scope; `report` opens it on Trend and `log` on Log. The newest card redraws as subagents report; the cards before it keep their header and bar. There are no keys and no buttons in the card, and none of the terminal's 🔀, teal and model colours.

The keys work as soon as the view opens, with no click:

Key	Does
Tab, Shift+Tab	Next or previous tab, wrapping at both ends
↓, ↑	Next or previous window: last 24 hours, 7 days, 30 days, all time
`d`, `w`, `m`, `a`	That window directly
`p`	Switches between your data across projects (user) and this project's
`o`	Opens the report page in your browser (section 3.7)
`r`	Refreshes: runs compaction and reads again
`l`	Opens the event log: from a terminal in the system's default app, its path written as a line in the session, with the `archive/` folder when there is one
Page Up, Page Down	Scroll a long tab
Esc	Closes the view

From a terminal the log is opened with `open` on macOS and `xdg-open` on Linux. With no log yet, on another system or in a hosted session nothing is opened: the line says why and gives the path. A log that compaction has just rotated away opens its `archive/` folder instead.

← and → do not switch tabs, as they do in Claude Code's own dialog: Claude Code does not pass them to a plugin's pane, and ← at the prompt opens the agents view.

Opening the view runs compaction for at most 3 seconds; if it takes longer, the view shows the numbers as of the last compaction and says so. Where no pane can be placed (`claude -p`, a headless run, a terminal under 60 columns), the command prints the same rows as text, without colours but with the status dots: the tab you named, or all four, under a 🔀 `Usage · <window> · <level>` title. Every answer is for you only: the model does not read it.

The KPI tiles

Overview opens with four tiles for the window and level; Models and Classes show them too when the four fit on one row (70 columns). Each compares the window with the window of the same length just before it (`all` has no comparison): the change is green when better and red when worse, and a status dot tells how the number reads.

Tile	Shows	Status dot
FPY	First-pass yield, and its change in points (▲, ▼)	🟢 `good` from 85%, 🟡 `fair` from 70%, 🔴 `poor` below
$/success	Cost per successful task, and its change in percent	🟢 `cheaper` or 🔴 `dearer` than the window before, 🟡 `same`; ⚪ `no prior` with no earlier window to compare with (always for `all`)
Rework	Rework rate, and its change in points	🟢 `low` up to 10%, 🟡 `some` up to 25%, 🔴 `high` above

Tile	Shows	Status dot
Routed	Subagent starts, and the router's ↓ downgrades, ↑ upgrades and = keeps	none

A change of zero shows `=`. A tile over fewer than five tasks shows ⚪ `weak`: too few to read. Under the tiles, two **sparklines** draw FPY and cost per success across the window, oldest first, each ending with its latest value; then one FPY bar per tier and effort, coloured as the FPY dot (grey under five tasks).

Overview




Figure 8. Overview: routing, measuring and adapt status; the KPI tiles, the sparklines and the FPY bars of the last 7 days; this session's subagents by model with their tokens and cost; this session's routing decisions by action. Here the week was worse than the one before (FPY down 6 points, cost per success up 58%), and the session ran the three subagents of Figure 7.




Figure 8b. The Model routing card in the Claude desktop app, on Overview: the heatmap of tasks per day, the key figures and the routing decisions by kind.

Models




Figure 9. Models: the tiles, then per tier and effort over the window, closed tasks, tokens, cost, FPY with a bar, cost per successful task, and the model ids seen.




Figure 9b. The card on Models: a row per model with its share of tasks and the figures per effort level, then tasks per day by model.

Classes



Figure 10. Classes, last 7 days, user level, under the tiles. Each class has a summary line, then a line with the grid's choice next to the best measured cell (yellow when it differs) and its weak-signal flags, then its cells; `*` marks the recommended one. Up to three recommendations that differ from the grid close the tab, each led by its FPY.

Read Figure 10 this way. For `edit-specified`, `sonnet·low` was right first time in 80% of 5 tasks at $0.055 per success, against 63% and $0.090 for the grid's `sonnet·medium`: the cheaper cell is recommended, and the line turns yellow with `(differs)`. For `review-debug`, `opus·high` was right every time but costs more per success than `opus·medium`, so the grid's choice stands. `design-open` has no cell with three tasks yet: `not enough data`, and the `n < 5` flag marks it as a weak signal.




Figure 11. The same tab after `m`: the last 30 days. More tasks, steadier numbers: FPY and rework now read 🟢 `good` and `low`, and both changes are green, while cost per success rose 5%. The `all` window (`a`) shows the aged aggregates, the very numbers of the report page; shorter windows count the tasks whose report fell inside them.




Figure 12. After `p`: the project level, here the `product` repository, over 30 days.

Decisions




Figure 13. Decisions: the latest twelve routing decisions of every session (UTC): action, the model before → the tier and effort after, the subagent type and the reason. `•` marks this session's.




Figure 13b. The card on Decisions: the decisions by kind as a bar and a legend, with the latest of the kind that is open.




Figure 14. `/model-router help`.

3.7 The report page

The same numbers on a page, for a longer look or to keep: ask for the *model-router report* (the `report` skill), type `/model-router report`, or press `o` in the view.

In a terminal the script compacts the event log, writes `<config dir>/model-router/report.html` and the system's default browser opens it (`open` on macOS, `xdg-open` on Linux). The answer says that the page opened and gives its path; when nothing could open it, it says why.

In the Claude desktop app (and in VS Code and the mobile apps) `/model-router report` opens the Model routing card on Trend, with the weekly figures as bars; the card writes the same page and links it in its last line, to open, keep or share.

From a shell:

```
node "<plugin folder>/scripts/report.mjs"             # write and open
node "<plugin folder>/scripts/report.mjs" --no-open   # write only (remote or headless)
```




Figure 15. The top of the report page, with sample data: the Savings section of the last 30 days, with its verdict, its four cards, the spend per week, the judge's figures and the saving per pair of models. Further down, the page has the headline (the KPI cards of the usage view), the weekly trend, the routing decisions by action, one card per class at the user level and the projects. The page follows the system's light or dark theme.



Figure 15b. In the Claude desktop app `/model-router report` opens the card on Trend: right first time and cost per success per week, with the page linked in the last line.




Figure 15c. `/model-router log` opens the card on Log: the records by kind and per day, the latest of the kind that is open, and `events.jsonl` linked in the last line.

The page reads top to bottom:

- **Savings.** The last 30 days: what the subagents cost against what the same tasks would have cost on the model of the session that started them. A verdict (`pays off`, `not proven` or `costs more`) with its reason, then four cards: the cost per successful task with its baseline and the share saved; the amount saved; the share of tasks moved to a cheaper model; whether their quality holds. Under them, the spend per week against the baseline, the judge's calls and time, and the saving per pair of models. A verdict needs at least 100 tasks compared. Only tasks started from release 0.7.0 on are compared: their records name the session's model and the tokens by kind, from which the page reads back each model's prices. The terminal's usage view has the same figures on its Savings tab.
- **Headline.** The last 30 days: the same four KPI cards as the usage view on `30d` (first-pass yield, cost per successful task, rework, routed starts) with their status, their change against the 30 days before and a small chart, then the models of the window. With fewer than five scored tasks one notice says the figures are indicative.

- **Trend by week.** FPY and cost per successful task per week, as two charts and a table. With up to three weeks the charts draw one bar per week.
- **Routing decisions.** Every decision logged, counted by action.
- **Classes.** One card per class, all projects together: the grid's choice, the recommendation, and a row per tier and effort with tasks, FPY, rework, cost per task, cost per success and the explored share. ★ marks the recommended cell; ○ and grey text mark a row with fewer than five tasks.
- **Projects.** The same cards per project, folded under the project's path: click a path to open it. With a single project whose figures are the ones above, one line says so.

Tasks are whole counts. In the class cards FPY, rework and cost weigh a recent task more than an old one (`halfLifeDays`); hover a count to see the weighted count behind it. The footnote of the page names the folder the data was read from.

The page and the usage view share one aggregation, so their numbers agree. The page is self-contained, with no script and nothing fetched, and is written locally; share it only if you mean to. It reads at the width of a side pane: under 560 pixels the tables drop the bars, the cost per task and the explored share. The *Explored* column stays at 0% before release 0.4.

3.8 Options

The mod's options (`userConfig` in its `plugin.json`). Set them in `/config`, or under `pluginConfigs` in a settings file, keyed by the installed plugin:

```
{
  "pluginConfigs": {
    "model-router@mrbogomips": {
      "options": { "reworkWindowMin": 45, "deepModel": "opus" }
    }
  }
}
```

Option	Default	Meaning
`fastModel`, `balancedModel`, `frontierModel`, `deepModel`	`haiku`, `sonnet`, `fable`, `opus`	Models behind the judge's fast, balanced, frontier and deep tiers; the fast one also runs the judge
`minDowngradeConfidence`	0.6	Judge confidence needed to lower the model, or to set effort `low`
`minUpgradeConfidence`	0.3	Judge confidence needed to raise the model, or to set effort `medium`, `high` or `xhigh`
`minFrontierConfidence`	0.7	Judge confidence needed to send a `design-open` task to the frontier tier; below it, or for any other class, the start gets the deep tier
`riskThreshold`	0.7	Risk above which the start gets the deep tier and at least `high` effort
`timeoutMs`	8000	Judge time limit; past it the start is left unchanged
`routeSubagents`	true	Route subagent starts at all

Option	Default	Meaning
`measure`	true	Record the event log and the quality data
`adapt`	false	Choose from the quality data; from release 0.4, unused before
`halfLifeDays`	30	Aging of the quality data
`projectPriorStrength`	5	How many observations the user level counts for in a project's estimate; from 0.4
`exploreCap`	0.1	Share of decisions per class that may explore; from 0.4
`reworkWindowMin`	30	Minutes after a report during which a redo counts as rework
`similarityThreshold`	0.5	Word overlap at which two task descriptions count as the same task

The mod saves the options compaction uses (`halfLifeDays`, `reworkWindowMin`, `similarityThreshold`, `projectPriorStrength`) to `options.json` at each session start when `measure` is on, so the report script uses the same values.

3.9 What is recorded, and where

The recorded data stays on your machine. Everything lives under `<config dir>/model-router/` (`CLAUDE_CONFIG_DIR`, else `~/.claude`); nothing is written inside a repository.

File	Content
`events.jsonl`	Append only, until it is rotated into `archive/`: routing decisions; each subagent start with its type, name and short description; the paths of files the session and its subagents write; tool names of failed subagent calls and stop targets; the first 2,000 characters of the two prompts you type next after a subagent reports, inside the rework window, and of no other prompt; reports with tokens and estimated cost; session ends; outcomes (written by compaction).
`archive/`	The event log once it reaches 32 MB, rotated by compaction: kept with its outcomes, routing decisions and subagent starts only (the prompt text is dropped), and with its outcomes only after 90 days. The report and `/model-router` read it with `events.jsonl`.
`options.json`	The options compaction uses
`quality/user.json`, `quality/projects/<id>.json`	Aggregates per user and per project, with the project's root path
`quality/state.json`, `quality/.lock`	Compaction's position in the log, and its lock (stale after 2 minutes)
`report.html`	The report page

The judge is one fast-tier model call per routed start through your session's own client, counted in the session's cost: like any other request of the session, its input (the subagent type, its short description and the first 4,000 characters of its task) goes to the model provider. Turn recording off with `measure: false`; to reset the data, delete `<config dir>/model-router/` (the event log is append-only and never trimmed).

3.10 Limits

- The mod needs Claude Code 2.1.329 or later; the skills do not need the mod.
- Only starts made through the `Agent` tool are routed. An agent defined by a plugin is never routed; of the built-in types only `general-purpose` and `Explore` are.
- The router picks `fable` only for `design-open` work, and it compares with the parent's model, so a subagent of a `fable` session can be lowered. Up to 0.3 it does not hold `review-debug` and `design-open` to the grid's floor.
- Costs are the engine's estimates. Edits made outside the session's own tools are not seen.
- Several `Agent` calls made in one message are drawn by Claude Code as one *N background agents launched* row: the 🔀 lines then show only in the ctrl+o transcript, under each call.
- Up to 0.3 the data is measured, not used: `adapt`, `projectPriorStrength` and `exploreCap` take effect from 0.4.

4. Troubleshooting and FAQ

`/session-hub` or `/model-router` is an unknown command.
The mod is not loaded: mods are off, or Claude Code is older than 2.1.329 (`claude --version`). Without the mod, `session-hub`'s skills, scope guard and record still work, and the `model-router` skills too: ask for the *model-router report* instead of the view.

Are my children guarded with mods off?
Their `Edit`, `Write` and `NotebookEdit` calls are, by the hook. Shell writes and messages to siblings are then held back by the handoff's rules alone.

Does routing work in auto permission mode?
Yes. The router never changes the `Agent` call that auto mode reviews; it sets the model when the subagent starts and the effort on each of its model requests.

A child's messages wait for my approval, or expire.
The sender and the receiver differ on bypassing permission prompts: the receiver holds the message for you (five minutes by default). Children start in the master's mode to avoid this; if you chose another mode, approve the messages, or set `crossSessionInbound` (`accept`, `hold`, `refuse`) for that child, for example `--settings '{"crossSessionInbound":"accept"}'`.

Every write in a child is blocked, even inside its folder.
Read the message after `[session-hub] Write blocked:`. An unknown `SESSION_HUB_ROLE` value (anything but empty, `none`, `master` or `child`) blocks every write; so does a missing, relative or non-existent `SESSION_HUB_SCOPE_ROOT`, a root of `/` or the home folder, or `node` missing from `PATH` (*the scope guard could not run*). Fix the launch command. A path inside the folder that is a link to another place is blocked by design.

A child stopped at a trust prompt, or `claude --bg` says `Workspace not trusted`.
Trust is per repository and is not inherited from the hub. Open the repository once with `claude` and accept the prompt, or answer it in the child's window; then let the master retry.

I resumed a child and the guards are gone.
The role comes from the launch environment. Resume with the same `SESSION_HUB_*` variables in front of `claude --resume`.

The panel shows `not listed` for a child that runs.
The live status comes from the session list. A child started with another configuration folder or account, on another machine, or in the desktop app may not be listed; it also cannot message the master.

The children record is reported as corrupt.
The script never overwrites a file it cannot read. Fix or move the file (its path is in the message); the work goes on without recording meanwhile.

Lines like `session-hub: its prompt.compose hook was skipped` appear.
An organization's managed mod runs first and passed the event on without the plugin's hooks. The plugin falls back to sending the scope line as context; nothing to do.

The report or the Classes tab is empty.

Check that mods are on and that `measure` is on (the default). A task counts only once its rework window has closed (30 minutes after its report) or its session has ended. Cancelled, risky, untagged, unknown-model and unknown-effort tasks are measured but not learned. If another compaction was running, the page shows the data from before it: run it again in a minute.

A subagent was not routed.

It carried a model, was a fork or a resume, named an agent with a fixed model or a plugin's agent, or routing was off (`/model-router off`, `routeSubagents: false`, or `CLAUDE_CODE_SUBAGENT_MODEL` set). The Decisions tab shows the reason of each decision.

No 🔀 line under an `Agent` call.

The mod is not loaded (see the first answer), the start was refused, or several calls were made in one message and are drawn as one row: press ctrl+o to see each call with its line. The line appears once the subagent has started.

The project level shows nothing.

The project is the git remote of the session's folder, else its root. Data recorded under another folder or remote belongs to another project; the user level shows everything.

An agent asked for `max` effort, or a model outside the grid.

The grid never uses `max`; `setup` shows a value outside the grid back to you with the nearest valid one. An explicit choice you make in the conversation always wins.

5. Quick reference

Skills

Skill	Ask for it with
`session-hub:setup`	"set up session-hub for this hub"
`session-hub:dispatch`	a task touching the hub's repositories; a `[<task> <repo>]` message; "status of the children"
`session-hub:spawn`	"start a child in product for T-42"
`model-router:choose-model`	meant to load before any start; "use the model-router grid"
`model-router:setup`	"set up model routing for this project"
`model-router:report`	"show the model-router report"

Commands and keys

Command or key	Does
`/session-hub`	role and scope; in a master the children table and panel
`/session-hub log`	opens the children record (a file from a terminal, the card on Record in the desktop app)
`/session-hub help`	help
`/model-router [tab] [24h|7d|30d|all] [user|project]`	usage view; tabs `overview`, `models`, `classes` (`stats`), `decisions`
`/model-router on` | `off` | `report` | `log` | `help`	routing for this session; report page; event log; help
Tab, Shift+Tab	next, previous tab
↓, ↑ · `d` `w` `m` `a`	next, previous window · window 24h, 7d, 30d, all
`p` · `o` · `r` · `l` · Page Up/Down · Esc	user/project · report · refresh · event log · scroll · close

Messages

`[<task> <repo>] <type>: <text>`	child to master; type `question`, `out-of-scope`, `pr`, `done`, `abandoned`
`[master] …`	master to child
`[mr:<class>]`, `[mr:<class>!]`	class tag at the start of a subagent's description; `!` when risky
🔀 `<model> <bar> <effort> -> <reason>`	choose-model line: before a start (skill), and in colour under the `Agent` row with what the subagent got (mod)

Variables

`SESSION_HUB_ROLE`	`child`
`SESSION_HUB_MASTER`	master's session name
`SESSION_HUB_SCOPE_ROOT`	write root, absolute
`SESSION_HUB_HANDOFF`	handoff file, absolute

`SESSION_HUB_REGISTRY`	children record, absolute
`SESSION_HUB_GUARDS`	`on` (default) or `off`
`CLAUDE_CONFIG_DIR`	config folder (else `~/.claude`) holding both plugins' state

Hub keys (`## Child sessions`)

Repositories · Task IDs · Propagate · Master only · Model · Effort · Scope · Registry · Guards (`on`) · Environment (`auto`) · Layout (`ask`) · Worktrees (`repo`) · Session name (`<task>-<repo>`)

Options (`model-router`)

`fastModel` haiku · `balancedModel` sonnet · `frontierModel` fable · `deepModel` opus · `minDowngradeConfidence` 0.6 · `minUpgradeConfidence` 0.3 · `minFrontierConfidence` 0.7 · `riskThreshold` 0.7 · `timeoutMs` 8000 · `routeSubagents` true · `measure` true · `adapt` false · `halfLifeDays` 30 · `projectPriorStrength` 5 · `exploreCap` 0.1 · `reworkWindowMin` 30 · `similarityThreshold` 0.5

Files

`<config dir>/session-hub/children-<hub id>.json` (+ `.lock`)	children record
`<scratchpad or mktemp -d>/<name>-handoff.md`	a child's handoff
`<config dir>/model-router/events.jsonl`	event log
`<config dir>/model-router/options.json`	options for compaction
`<config dir>/model-router/quality/user.json`, `projects/<id>.json`	aggregates
`<config dir>/model-router/quality/recommendations.json`	hints, read if present (no release writes it yet)
`<config dir>/model-router/report.html`	report page
Hub's `AGENTS.md` (or `CLAUDE.md`), `## Child sessions`	hub configuration
Project's `AGENTS.md` (or `CLAUDE.md`), `## Model routing`	project defaults

Scripts

`node <session-hub folder>/scripts/registry.mjs read --hub <dir>`	print the children record
`node <model-router folder>/scripts/report.mjs [--no-open]`	compact and write the report
`node <model-router folder>/scripts/compact.mjs`	compact the event log

An installed plugin's folder is listed by `claude plugin list`, or found under `<config dir>/plugins/`.